

Personal Air Sampling Pumps

Quick find features chart

SKC Air Sampling Pumps are offered with a variety of features, in different sizes and to suit all budgets.

View our quick-find feature chart, then check the specifications on the following pages. We feel confident we'll have the pump for you.



PUMP FEATURES	AirChek 2000	Sidekick	Airlite	Universal TX	Universal XR	Pocket	Workhorse	Legacy
Page	13	15	15	17	17	18	19	20
Flowrate (mls/min)	5-3250	5-3000	5-3000	5-4000	5-5000	20-225	50-200	5-15000
Approx Weight (grams)	624	340	340	964	964	142	340	1036
Intrinsic Safety	UL	ATEX	non I/S	ATEX	UL	ATEX	UL	
Corrects for changes in atmospheric pressure	✓							✓
Battery	NiCaD	NiCaD	Alkaline	NiCaD	NiCaD	NiMH	NiCaD	Lithium Ion
PC Compatible	✓					✓		✓
Programmable	✓			✓	✓	✓		✓
Timer or Clock	✓	✓		✓	✓	✓		✓
Suggested Applications	gas/dust	gas/dust	gas/dust	gas/dust asbestos	gas/dust asbestos	gas	gas	bioaerosol
Ready to order Kits	K KP KV KC					KV		K



For ready to order kits - have a look at pages 7-11

superior flow control systems

programmable models

rugged and compact

reliability assured

IMPORTANT

Features specified in the quick find guide may apply to specific model(s) in the range only.

A constant pressure controller and/or adjustable tube holder may be needed for low flows - (5-500 mls/min).

Intrinsic safety ratings apply to selected models in each range.

To verify that you are choosing the correct pump, **always** refer to individual pump details and if in doubt telephone SKC customer services to discuss your requirements before making your purchase.

We're always happy to help!